

## MAJOR PRODUCTS FOR REGULAR ACQUISITION

### A. AGRICULTURAL SECTION

#### 1. WHITE TABLE EGGS

Composition	Per Egg	Protien	Fat	Moisture	Calcium	Phosphorus	Vit. A	Thiamin	Vit. B6	Vit. E	vit. D
	100 ml	12.33 gm	9.95 gm	75.81 gm	62 mg	193 mg	570 iu	0.067 mg	0.188 mg	0.72 mg	105 iu

General Descriptior White Table Eggs

Appearance: Glossy White

Shelf Life: 3 mos. From production @ 4-7°C and 75-80% humidity of sorrounding environment

Feed Composition: As per the required specification of the Saudi Ministry of Agriculture

Packing	Size	Weight (gm.)	Tray/Carton	Qty/Carton	Gross Wt. (kg.)
	Small	40-50	12 trays	360	19.4
	Medium	50-60	12 trays	360	23
	Large	60-70	12 trays	360	26.6
	Xlarge	70-80	12 trays	360	30

## 2. FERTILE HATCHING EGGS

Breed	Ross "308"
Age Of Flock	31-42
Egg Weight	58-63 grams
Fertility (Min)	90%
Hatchability (total consignment ave.)	80%
Breakage (Min)	1%
Max. age of hatching eggs on packing date	3 days
Vaccination	
Egg Quality	Clean eggs but not washed
Clinical Sign of Diseases at present	Free from clinical sign of any infectious disease
	Fowl Pox, Fowl Cholera
	Ornithosis/ Psittacosis, Marek's Disease
	Avian Leukosis
No evidence of Disease during the past nine months	Infectious Laryngotracheitis
	Infectious Bronchitis
	Avian Encephalomyelitis
	Mycoplasmosis (Chronic Respiratory Diseases)
Free from disease	Salmonella Pullorum (Pullorum Disease)
No outbreak of disease for the past nine months within a radius of 10 Kms	New Castle disease
	Highly Pathogenic Avian Influenza (Fowl Plague)
Validity of Health Certificate	30 days from the date of issue

## B. INDUSTRIAL SECTION

### 1. EXAPANDABLE POLYSTYRENE RAW MATERIALS

TECHNICAL SPECIFICATION:

Grade	Bead Size	Density Range	Application					
			Shape Mould				Block Mould	
	mm	Kg/m <sup>3</sup>	Vegetable Box	Fish Box	Block Inserts	Eco Board	Pure Blocks	Mixed Blocks
EPS 450	0.4-0.8	18-35						
EPS 552	0.6-1.1	17-30						
EPS 763	1.2-2.5	15-20						
EPS 652	0.9-1.4	16-25						

### 2. PREPAINTED GALVANIZED STEEL COIL

TECHNICAL SPECIFICATION:

THICKNESS (MM)	0.25	0.3	0.32	0.35	0.38	0.4	0.28	0.3	0.32	0.35	0.35	0.4
WIDTH (MM)	1219						1085					

#### HOT DIPPED PGI ASTM A653/C TYPE B G30

Top colour Polyester in Cloud White @ 5 microns primer + 15 microns polyester

Back Colour Polyester Off white @ 5 microns primer + 5 microns polyester

Zinc Mass Z90gm/m<sup>2</sup> @ both sides

Tolerance SASO ASTM A924M